

MODELES	PUISSANCE	DEBIT	PRESSION	GARANTIE
27	22 - 250 kW	6,08 - 67,95 m3/min	3 - 5 bar	5 ans - pieces 10 ans

Du plus petit au plus grand modele

Modele	Debit m3/min	Puissance kW	Pression bar	Bruit dB(A)	L x l x H mm	Poids kg	Raccord	Tension	Entrainement	Demarrage
CZ-SLTLS-22S	2,9 - 6,47	22	3/4/5	62	1415x1030x1330	1330	DN50	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLT-22T	2,74 - 6,08	22	4/5	65	1610x1050x1380	1100	DN40	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLS-30S	4,21 - 9,37	30	3/4/5	65	1900x1200x1650	1420	DN65	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLT-30T	3,74 - 8,33	30	4/5	65	2020x1290x1600	1200	DN50	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLS-37S	5,08 - 11,29	37	3/4/5	65	1900x1200x1650	1420	DN65	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLT-37T	4,5 - 10,02	37	4/5	65	2020x1290x1600	2000	DN50	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLS-45S	5,71 - 12,7	45	3/4/5	68	2160x1450x1750	1900	DN80	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLT-45T	6,43 - 13	45	4/5	65	2285x1500x1710	2100	DN50	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLS-55S	7,07 - 15,72	55	3/4/5	68	2160x1450x1750	1900	DN80	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLT-55T	7,35 - 16,35	55	4/5	65	2285x1500x1710	3500	DN65	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLS-75S	9,82 - 21,84	75	3/4/5	68	2900x1830x2000	2700	DN125	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLT-75T	9,37 - 20,84	75	4/5	68	2285x1500x1710	3750	DN65	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLS-90S	11 - 24,65	90	3/4/5	73	2900x1830x2000	3800	DN125	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLT-90T	11,63 - 25,85	90	4/5	70	2800x1700x1950	3800	DN80	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLS-110S	13,56 - 30,15	110	3/4/5	74	2900x1830x2000	4000	DN125	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLT-110T	14,44 - 32,11	110	4/5	72	2820x1730x2100	4200	DN80	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLS-132S	16,38 - 36,41	132	3/4/5	76	2900x1830x2000	4800	DN125	400V/50Hz/3Ph	Direct	Y-

Modele	Debit m3/min	Puissance kW	Pression bar	Bruit dB(A)	L x l x H mm	Poids kg	Raccord	Tension	Entrainement	Demarrage
CZ-SLTLT-132T	17,34 - 38,54	132	4/5	74	2820x1730x2100	5000	DN125	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLS-160S	18,66 - 41,48	160	3/4/5	76	3500x2030x2230	4800	DN150	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLT-160T	20,16 - 44,8	160	4/5	76	3450x2000x2050	5900	DN125	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLS-185S	19,81 - 44,03	185	3/4/5	76	4250x2280x2550	7000	DN200	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLT-185T	23,54 - 52,3	185	4/5	76	3450x2000x2050	5900	DN150	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLS-200S	20,96 - 46,59	200	3/4/5	76	4250x2280x2550	8000	DN200	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLT-200T	25,81 - 57,36	200	4/5	80	3800x2250x2350	7800	DN150	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLS-220S	26,9 - 59,78	220	3/4/5	77	4250x2280x2550	8000	DN200	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLT-220T	27,9 - 62,01	220	4/5	80	3800x2250x2350	8000	DN150	400V/50Hz/3Ph	Direct	Y-
CZ-SLTLT-250T	30,58 - 67,95	250	4/5	80	3800x2250x2350	8100	DN150	400V/50Hz/3Ph	Direct	Y-